

PROJECT	
SUBSTRATE	<b>NEW CONCRETE BLOCK-WORK OR BRICK WORK</b>
RENDER	<b>K-REND SILICONE WP/FT (SILICONE ENHANCED, WATER REPELLENT, THROUGH COLOURED TEXTURED RENDER).</b>
THE BILL ITEM	K-Rend render, one coat, total finished thickness 18mm, applied to concrete block walls or brickwork, in accordance with manufacturer's instructions. <b>One Coat:</b> K-Rend Silicone WP/FT – 18mm thick Colour as selected by the Specifier.
SPECIFICATION CLAUSE	M20
PLASTERED, RENDERED, ROUGHCAST COATINGS	To be read with Preliminaries/General Conditions
TYPE(S) OF COATING	M20-165
PROPRIETARY RENDER	Manufacturer and Reference: "K-Rend" by Kilwaughter Chemical Co Ltd Tel. 028 2826 0766 <b>Location:</b> External Walls as indicated on the elevations. <b>Background:</b> Common brickwork or concrete block-work <b>First Pass:</b> K-Rend Silicone WP/FT, ruled to line and level. <b>Thickness:</b> 6-8mm <b>Second Pass:</b> K-Rend Silicone WP/FT, 10-12mm thick, applied by trowel. Rule to line and level and allow to set. Scratch back to 10mm with tool supplied. Brush surface. <b>Total Thickness:</b> 16-18mm <b>Finish:</b> Textured <b>Note:</b> The passes are applied wet on wet, monolithic with each other. All of the above in accordance with manufacturer's instructions.
SUPPLIER	Kilwaughter Chemical Company Ltd.

ISSUE DATE OCTOBER 2001  
E & O E