

PROJECT	
SUBSTRATE	NEW CONCRETE BLOCK-WORK OR BRICK WORK
RENDER	K-REND SILICONE WP/FT (SILICONE ENHANCED, WATER REPELLENT, THROUGH COLOURED TEXTURED RENDER).
THE BILL ITEM	<p>K-Rend render, two coats, total finished thickness 18mm, applied to concrete block walls or brickwork, in accordance with manufacturer's instructions.</p> <p>First Coat: K-Rend Standard Base Coat – 8mm thick; Second Coat: K-Rend Silicone WP/FT – 10mm thick Colour as selected by the Specifier.</p>
SPECIFICATION CLAUSE	M20
PLASTERED, RENDERED, ROUGHCAST COATINGS	To be read with Preliminaries/General Conditions
TYPE(S) OF COATING	M20-165
PROPRIETARY RENDER	<p>Manufacturer and Reference: "K-Rend" by Kilwaughter Chemical Co Ltd Tel. 028 2826 0766</p> <p>Location: External Walls as indicated on the elevations. Background: Common brickwork or concrete block-work. Undercoat: K-Rend Standard Base Coat, ruled to line and level. Lightly scratch and allow to set. Thickness: 8mm Final Coat: K-Rend Silicone WP/FT, 12mm thick, applied by trowel. Rule to line and level and allow to set. Scratch back to 10mm with tool supplied. Brush surface. Thickness: 10mm Finish: Textured</p> <p>All of the above in accordance with manufacturer's instructions.</p>
SUPPLIER	Kilwaughter Chemical Company Ltd.

ISSUE DATE OCTOBER 2001
E & O E