

PROJECT	
SUBSTRATE	NEW CONCRETE BLOCK-WORK OR BRICK WORK
RENDER	K-REND SILICONE WP/FT (SILICONE ENHANCED, WATER REPELLENT, THROUGH COLOURED TEXTURED RENDER).
THE BILL ITEM	K-Rend render, one coat, total finished thickness 18mm, applied to concrete block walls or brickwork, in accordance with manufacturer's instructions. One Coat: K-Rend Silicone WP/FT – 18mm thick Colour as selected by the Specifier.
SPECIFICATION CLAUSE	M20
PLASTERED, RENDERED, ROUGHCAST COATINGS	To be read with Preliminaries/General Conditions
TYPE(S) OF COATING	M20-165
PROPRIETARY RENDER	Manufacturer and Reference: "K-Rend" by Kilwaughter Chemical Co Ltd Tel. 028 2826 0766 Location: External Walls as indicated on the elevations. Background: Common brickwork or concrete block-work First Pass: K-Rend Silicone WP/FT, ruled to line and level. Thickness: 6-8mm Second Pass: K-Rend Silicone WP/FT, 10-12mm thick, applied by trowel. Rule to line and level and allow to set. Scratch back to 10mm with tool supplied. Brush surface. Total Thickness: 16-18mm Finish: Textured Note: The passes are applied wet on wet, monolithic with each other. All of the above in accordance with manufacturer's instructions.
SUPPLIER	Kilwaughter Chemical Company Ltd.

ISSUE DATE OCTOBER 2001
E & O E